

| 形式<br>記号 | 線心数 | 導体<br>構成                     |         |          | 絶縁体<br>厚さ<br>mm | 最大<br>仕上<br>外径<br>mm | 導体<br>抵抗<br>(20°C)<br>Ω/km | 試験<br>電圧<br>V・1分 | 絶縁<br>抵抗<br>(20°C)<br>MΩ・km | 許容<br>電流<br>(75°C)<br>A | 標準<br>長さ<br>m |
|----------|-----|------------------------------|---------|----------|-----------------|----------------------|----------------------------|------------------|-----------------------------|-------------------------|---------------|
|          |     | 公称<br>断面積<br>mm <sup>2</sup> | 素線数/素線径 | 外径<br>mm |                 |                      |                            |                  |                             |                         |               |
| WL2H     | 1   | 0.15                         | 7/0.16  | 0.5      | 標準1.0           | 2.70                 | 134                        | 2500             | 200                         | 5                       | 200           |
|          |     | 0.2                          | 7/0.20  | 0.6      | 1.0             | 2.80                 | 86.0                       | 2500             | 200                         | 6                       | 200           |
|          |     | 0.3a                         | 12/0.18 | 0.75     | 1.0             | 3.00                 | 61.9                       | 2500             | 200                         | 7.5                     | 200           |
|          |     | 0.3b                         | 7/0.26  | 0.8      | 1.0             | 3.00                 | 50.3                       | 2500             | 200                         | 8.5                     | 200           |
|          |     | 0.5                          | 19/0.18 | 0.9      | 1.0             | 3.20                 | 39.1                       | 2500             | 200                         | 10                      | 200           |
|          |     | 0.75                         | 30/0.18 | 1.2      | 1.0             | 3.50                 | 24.8                       | 2500             | 200                         | 13                      | 200           |
|          |     | 1.25                         | 50/0.18 | 1.5      | 1.0             | 3.90                 | 14.9                       | 2500             | 200                         | 18                      | 200           |
|          |     | 2.0                          | 37/0.26 | 1.8      | 1.0             | 4.20                 | 9.52                       | 2500             | 200                         | 23                      | 200           |
|          |     | 3.5                          | 45/0.32 | 2.5      | 1.2             | 5.40                 | 5.17                       | 2500             | 200                         | 33                      | 100           |
|          |     | 5.5                          | 35/0.45 | 3.1      | 1.4             | 6.40                 | 3.37                       | 2500             | 200                         | 45                      | 100           |
|          |     | 8.0                          | 50/0.45 | 3.7      | 1.4             | 7.00                 | 2.35                       | 2500             | 200                         | 56                      | 100           |
|          |     | 14.0                         | 88/0.45 | 4.9      | 1.6             | 8.60                 | 1.34                       | 2500             | 200                         | 79                      | 100           |

